



**OUTLINE**

Lens Specifications - NMV - 50			
Specifications	Value	1/2"	1/3"
Focal Length	f = 50mm		
Maximum diameter (Ratio)	F = 1.4:1 ~ 16 ~ Close		
Picture Size	12.8 x 9.6mm	8.8 x 6.6mm	6.4 x 4.8mm
Angle - Vertical	10.8 deg.	7.54deg.	5.49 deg.
Horizontal	14.5 deg.	10.0 deg.	7.31deg.
Diagonal	18.0 deg.	12.5deg	9.12 deg.
Distortion (TV)	-0.05%	-0.05%	-0.02%
Minimum Focus Distance	0.5m		
Flange Back	17.526mm in air		
Back Focus	14.8mm in air		
Filter Screw Size	M40.5 x 0.5		
Effective Diameter - Front	35.0mm dia.		
- Rear	15.5mm dia.		
Mount	C-Mount		
Exit Pupil	-44.4mm dia.		
Temperature Range	- 10 ~ + 45 deg. C		
Strong Temperature Range	- 40 ~ + 60 deg. C		

UNLESS OTHERWISE SPECIFIED DIMENSIONS ARE IN INCHES AND INCLUDE CHEMICALLY APPLIED OR PLATED FINISHES

SCALE: 1.5:1

WEIGHT: See Table

DR: BE

CH:

PROJECT #: E2338

DATE DR: 7/13/2007

THE CONTENTS OF THIS DOCUMENT ARE PROPRIETARY TO NAVITAR. ITS USE IS AUTHORIZED ONLY FOR RESPONDING TO REQUEST FOR QUOTATION OR PERFORMANCE OF WORK FOR NAVITAR

0.0 inch 1.0

0.0 mm 25.0

DO NOT SCALE DRAWING

**NAVITAR**  
ROCHESTER, NEW YORK

LENS, 50.0mm FL, , 1.0", f/1.4

SIZE <b>B</b>	<b>NMV - 50M1</b>	REV <b>A</b>
SHEET 1 OF 1		